



B2420

Redesigned for improved ease- of- use.

The best-selling compact tractor is now even better.





| Model | B2420 |
|--|--|
| ROPS/CAB | ROPS |
| Engine | |
| Туре | E-TVCS, Liquid Cooled, 3 Cylinder diesel |
| Model | Kubota D1105 |
| Engine gross power | 17.9 kW |
| Engine power ECE-R24 | 15.8 kW |
| PTO power | 14.3 kW |
| No. cylinders | 3 |
| Rated speed rpm | 2600 |
| Bore & Stroke | 78 x 78.4 |
| Total displacement | 1123 cm ³ |
| Air cleaner | Double element |
| Muffler and exhaust pipe | Fully enclosed |
| Fuel tank capacity | 26 Litres |
| Drive Train | |
| Driving method | 2WD / 4WD |
| Transmission speeds | 9F3R |
| Max. travelling speeds | 19.4 Km/h |
| Differential lock | Standard |
| Brake type | Wet multi disk |
| Steering | Integrated power steering |
| PTO | miogration perior otee.mig |
| Rear PTO Type | Transmission driven with one way clutch |
| Rear PTO Speed | 540/960 rpm |
| Hydraulic system | - 10/000 Ipin |
| Pump capacity | 26.4 Litres per min |
| Lift control type | Select Q.I.V |
| Lift capacity @ link ends | 615 kg |
| Lift capacity @ Init crids Lift capacity @24" | 480 kg |
| Max. operating pressure | 135 kg/cm ³ |
| 3-point hitch | category |
| Hydraulic outlets | Hydraulic outlet only |
| Dimensions | Trydraulic outlet only |
| Overall length | 2815 mm |
| Overall width | 990-1331 mm |
| Overall height | 2300-2350 mm |
| Wheelbase | 1563 mm |
| Tread front | 797-815 mm |
| Tread rear | 734-1088 mm |
| | 267-313 mm |
| Ground clearance | |
| Turning radius with brake | 2.1 m 7-12 |
| Tyre 1 (Farm) -Front Tyre 1 (Farm) -Rear | 9.5-18 |
| | |
| Weight | 722-748 kg |
| Alternator Capacity | 40A |
| London | Indopendent Clampa |
| Headlamp Organisation deals | Independant 2 lamps |
| Operator's deck | Full flat, full rubber covered |
| Backlit instrument panel | Standard |
| Cup holder | Standard |
| *Operators noise level | 85.6 dBA |
| Safety frame | EC approved rear mount folerable ROPS |
| Options | |
| | |
| Rear work light kit Beacon lamp switch kit | Option Option |



