



For Earth, For Life  
**Kubota**

**L**

## KUBOTA DIESEL TRACTOR L1/L2 SERIES

L1421/L1501/L2351/L2421/L2501/L2602

The powerful new line up that offers an unbeatable package of class leading features to make your day easier and more productive.



# L1/ L2 Specifications

Series	L1					L2						
Model	L1-421		L1-501		L2-351	L2-421		L2-501			L2-602	
Cab/ROPS	ROPS		ROPS		ROPS	ROPS	Cab	Cab	ROPS	Cab	Cab	Cab
Engine												
Model name	V2203-M-E2-EU2	V2203-M-E2-EU1	V2403-M-TE2-EU1	V2403-M-TE2-EU2	D1803-M-E2-EU1	V2203-M-E2-EU2	V2203-M-E2-EU1	V2403-M-TE2-EU1	V2403-M-Te2-EU3	V2403-M-TE2-EU4	V2403-CR-TE4-EU2	
3Displacement l	2197 (4)		2434 (4)		1826(3)	2197 (4)		2434 (4)			2424 (4)	
Rated RPM rpm	2700		2600		2700	2700		2600			2600	
SAE Output (gross) KW/PS	33.5/45.5		36.5 / 49.6		27.3/57.1	33.5 / 45.5		36.5 / 49.6			45.8/62.3	
Transmission												
Type	FST	HST	FST	HST	FST	FST	HST	FST	GST	HST	HST	
F/R	8F/8R	3 range HST	8F/8R	3 range HST	16F/16R	16F/16R	3 range Dual Speed HST	16F/16R	24F/16R	3 range Dual Speed HST	3 range Dual Speed HST	
Creep gear	-	-	-	-	STD	STD	-	STD	-	-	-	
Max.Speed km/h	29.8	29.7	29.1	29.3	29.4	29.8	29.7	29.1	29.3	29.3	29.6	
PTO revolution												
Rear rpm	540				540/750	540/750	540	540/750	540	540	540	
Mid rpm	N/A				N/A	N/A	Option	N/A	N/A	Option	Option	
Steering	Hydraulic power steering											
3P control	Position control											
Dimensions												
Overall length (w/o 3P) mm	3170		3245		3015	3170		3245			3245	
Overall width (min. tread) mm	1485	1555	1470		1430	1485	1555	1470	1560		1560	
Overall height (w/ROPS) mm	2450	2250	2550		2415	2450	2250	2550	2365		2375	
Wheel base mm	1895		1915		1805	1895		1915			1915	
Min. ground clearance mm	390	360	400		360	390	360	400	405		392	
Tread Front mm	1145		1340		1150	1145		1340	1135		1135	
Tread Rear mm	1140-1310		1125 - 1325		1110-1385	1140-1310	1210 - 1410	1125-1325	1225-1325		1225-1325	
Turning radius (w/brake) m	2.7		3.2		2.7	2.7	2.7	3.2			3.2	
Weight kg	1635	1670	1805	1850	1545	1635	1775	1810	1805	1960	1995	2040
Fuel tank capacity l	50		54		44	50		54			51	
Standard tyre size	8-16		9.5 - 16		7-16	8-16		9.5-16			9.5-16	
Hydraulic												
Hydraulic control system	Position control											
Pump capacity l/m	37		35.6		31.5	37		35.6			35.6	
3-point hitch	SAE category 1		SAE category 1		SAE category 1	SAE category 1		SAE category 1			SAE category 1	
Max.lift force (at lift points)	1750				1700	1750		1750			1750	

## Front loader specification

Model	LA714EC	LA854EC	LA514EC	LA714EC	LA854EC	LA1054EC
Max. lift height (to bucket pivot pin) mm	2596	2863	2449	2596	2863	2863
Clearance with bucket dumped mm	1990	2255	1987	1990	2255	2255
Max. dump angle deg.	45	45	41	45	45	45
Max. rollback angle deg.	41	42	30	41	42	42
Lift capacity (pivot pin, max. height) kg	860	1129	613	860	1129	1129
Raising time sec.	3	4.2	2.7	3	4.2	4.2
Lowering time sec.	2.4	2.8	2.2	2.4	2.8	2.8
Bucket dumping time sec.	3	3.3	2.5	3	3.3	3.3
Bucket rollback time sec.	1.6	2.3	1.6	1.6	2.3	2.3



**KUBOTA (U.K.) LIMITED**  
 Dormer Road Thame, Oxfordshire, OX9 3UN.  
 Phone (01844) 268000



[www.kubota.co.uk](http://www.kubota.co.uk)

©2018 Kubota Corporation

Cat.No.4347-00-UK Printed in the UK. D.REX.'18-AUGUST.