

- Reinforced deck, fabricated in one piece 3mm steel plate
- Reinforced, structural frame across the body of the topper for absolute rigidity
- Galvanised headstock and skids for longer life
- Double jaw support lift arm brackets on TOP6
- Adjustable headstock for In-line and semi-offset on TOP3, TOP4 and TOP5 models
- Comer gearbox and boron steel blade carrier
- Shear bolt protected PTO shaft & convex skids
- Cat 1 pins on TOP3, TOP4 & TOP5
- Cat 1 & Cat 2 pins on TOP6
- TOP6 Semi offset only
- Wheel option available for TOP4 and TOP5





Code	ТОР3	TOP4	TOP5	TOP6
Tractor HP req'd	13	20	30	40
Transport width	1.17m	1.4m	1.65m	1.82m
No. of rotors	1	1	1	1
No. of blades	2	2	2	2
No. of gearbox	1	1	1	1
Gearbox rating	30hp	30hp	30hp	40hp
Weight	170kg	202kg	246kg	323kg



- Heavy duty semi-offset or in-line grass topper (6ft)
- Cat 2 pins
- Ideal for clearing heavy rushes and bracken
- 80hp gearbox
- shear bolt protection
- Heavy duty reinforced deck
- Heavy duty, boron steel blade carrier with high performance blades
- Galvanised skids and A frame
- Smooth top deck (no water traps)
- Optional chain rotor





Model	HP	Transport width	Rotors	Blades	Gearbox	Gearbox rating	Weight
тор6нс	90	1.8m	1	4	1	80hp	382kg





- 9ft standard model for topping meadows and grass
- Deck fabricated from 3mm steel plate with a reinforced structural frame across the topper body for rigidity
- HD galvanised chain support for secure transport
- Floating headstock and reinforced 4mm sides with convex galvanised skids gives constant ground contact and even cut
- Gearbox and rotors mounted on one piece HD central base plate with indestructible HD boron steel blade carriers
- HD 55hp Comer gear box with straight drive-line protected by rubber couplings
- PTO over-run and shear bolt protection against rotor impact
- Double jaw support lift arm brackets with Cat 2 lift arm pins





Super 900 model TOP9INHD & TOP9HDOF (2.7m) 9ft heavy duty models (For rushes and heavy grass)

- Fitted with 75hp gear boxes
- HD flexible knuckle drive line protected by rubber couplings
- Fitted with fluted blades and additional straight blades for mulching effect when cutting



TOP9HDOF (Front mounted model)

Model	HP	Transport width	Rotors	Blades	Gearbox	Gearbox rating	Weight
ТОР9	70	2.74m	2	4	3	55hp	494kg
TOP9INHD	80	2.74m	2	8	3	75hp	500kg
TOP9HDOF	80	2.74m	2	8	3	75hp	500kg



- Deck fabricated from 3mm one piece steel plate fitted on a reinforced, structural frame along the body of the topper for rigidity
- Floating top link and hinged body provide bi-lateral movement for constant ground contact and even cut
- Counter rotating twin rotors and indestructible boron steel blade carriers fitted with free floating, boron steel fluted blades
- Adjustable cutting height 50mm 200mm
- Converts to working/transport position hydraulically, with spring loaded safety latch when in transport position
- Hydraulic breakaway for the ultimate machine protection and speed of operation (can be reset from the tractor seat)
- Comer gearboxes with straight drive-line protected by rubber couplings
- PTO over-run and shear bolt protection against rotor impact
- Double jaw support lift arm brackets with Cat 2 lift arm pins





Model	HP	Transport width	Rotors	Blades	Gearbox	Gearbox rating	Weight
TOP7SF	70	1.83m	2	4	3	55hp	616kg
TOP8SF	80	1.83m	2	4	3	55hp	650kg

Heavy Duty Super Float Grass Topper TOP8SFHD (2.5m)



8ft heavy duty model for rushes and heavy grass

The heavy duty model has all the features of the standard super float but with additional features including:

- Fitted with 75HP gearboxes
- HD flexible knuckle drive line protected by rubber couplings
- Fitted with fluted blades and additional straight mulching blades



Model	HP	Transport width	Rotors	Blades	Gearbox	Gearbox rating	Weight
TOP8SFHD	80	1.83m	2	8	3	75hp	670kg

Trailed Superfloat Grass Topper TOP8T (2.5m) 8ft Standard



- Deck fabricated from 3mm one piece steel plate with reinforced 4mm sides & galvanised convex skids
- Free floating deck with spring assisted floatation allowing the deck to glide over the ground keeping the blades at an even cutting height at all times
- Counter rotating rotors combine with the fluted, hardened steel cutting blades to disperse grass evenly
- Gearboxes & twin rotors are mounted on a heavy duty one piece central base plate and fitted with indestructible boron steel blade carriers with free floating blade protection in the event of a collision
- Adjustable cutting height 50mm 200mm
- Converts to working/transport position hydraulically, follows directly behind the tractor
- Comer gearbox with straight drive-line protected by rubber couplings
- Lift arm drawbar combined with wide angle PTO c/w over-run and shear bolt protection for better manoeuvrability and tighter turning when operating
- 10.5 x 75 x 15.3 tyres on a reinforced wheel carriage

TOP9T 2.7m 9ft Heavy Duty For rushes and heavy grass


- Fitted with 75HP gearbox
- Heavy duty flexible knuckle drive line protected by rubber couplings
- Fitted with fluted & additional straight blades for mulching effect when cutting
- Hydraulic safety locking mechanism





Model	HP	Transport width	Rotors	Blades	Gearbox	Gearbox rating	Weight
TOP8T	80	2.5m	2	4	3	55hp	650kg
TOP9T	80	2.7m	2	8	3	75hp	850kg

Power Topper



- Double belt drive
- Electric start
- 20hp Honda GXV630 engine (2 year warranty)
- 1.2m cutting width with simple height adjustment
- Drawbar can be offset to either side with 5 different positions for hard to reach areas
- Galvanised for long life
- Boron steel rotor with hardened, free floating blades
- Removable jack
- Suitable for towing behind ATV's, quads or 4x4
- Heavy duty reinforced deck
- Half round skids
- Wheel size: 15x6-6





Model	HP	Transport width	Cutting width	Rotors	Blades	Wheels
TOP4P	20	1.3m	1.2m	1	2	15x6-6